

saunum



Smart sauna control unit

saunum leil 2.0

Saunum Leil is a next-generation smart sauna control unit that is convenient and easy to use. According to sauna data, Leil optimizes the sauna's heating time, reducing energy consumption. With three adjustable sauna modes, you can activate the heater with just a few taps on the screen. Once the sauna is ready, simply turn on the Saunum climate control system and enjoy an incredibly relaxing sauna experience with easy breathing and mild heat. As Saunum Leil also supports our AutoLeil automatic water dispensing solution, you can now operate and adjust this feature directly from the installed touch control panel. A ModBus integration option has also been added for connecting the device to smart homes.

Touch control panel



Leil button inside sauna room



Temperature selection:	temperature 40-100 °C
Heater run time:	adjustable up to 12 hours
Climate control system:	3 speeds. NB! Only use the climate device when you are in the steam room.
Pre-setting the sauna:	3 pre-set sauna modes (temperature, duration, climate device speed)
Sauna duration includes:	heating time that is approximately 1.5 hours, depending on your sauna
Sauna scheduling:	set the „sauna ready“ time and choose the sauna type. Repeating function available
Smart notifications:	real-time updates about sauna status and safety
Languages:	multi-language menu
Safety:	screen lock
Dimensions:	83 mm x 104 mm x 19.3 mm
Leil updates:	Saunum Leil Mobile included; optimized heating time; ModBus integration for smart home systems; control of Saunum AutoLeil via the dedicated touch control panel; included - Leil button for controlling the fan speed inside the sauna room.
Leil button:	Use to control the fan speed and air circulation of the sauna climate device directly from inside the sauna.

Remote control

With the Saunum Leil Mobile Set, you can control your sauna anytime and anywhere. You just need to pair the Saunum Leil application with your Leil Mobile Set that is connected to Wi-Fi network. Sauna notifications are displayed on the user's mobile phone screen.



Power unit

Supply voltage:	230 V 3 N~
Heater power:	up to 9 kW/ 12 kW (for higher power an additional contactor must be used)
Safety:	door sensor and overheating protection
Dimensions:	260 mm x 160 mm x 61 mm

2026 (1)